

Eliteaerosports SHOCKWAVE

original 2.6m length

VERSION	PRICE (20%VAT)	Export PRICE
SHOCKWAVE, - ENTRY	119,90 €	99,92 €
SHOCKWAVE, - STANDRD	209,90 €	174,92 €
SHOCKWAVE, - SPORT/POWER	289,90 €	241,58 €
SHOCKWAVE, - PRO	449,90 €	374,92 €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, -	- €	- €
, - SHOCKWAVE AFTERBURN	268,70 €	223,92 €
, - SPECIAL	- €	- €



ENTRY Kleinste Einsteigerversion bestehend aus 2-Kanal Steuerung, Landescheinwerfer(n) und einem (meist) weißen Blitzlicht

BASIC Besteht aus 4-Kanal Steuerung, Landescheinwerfer(n), Basis Beacon (ROT)/Blitzlicht (WEISS) und Positionslichtern (ROT+GRÜN)

STANDARD Besteht aus 4-Kanal Steuerung, Landescheinwerfer(n), Beacon (ROT), Positionslichter (ROT+GRÜN) und soweit sinnvoll ACL (WEISS). Grundausrüstung für eine preiswerte vorbildgetreue Beleuchtung

CIVIL/SPORT Diese Konfiguration nimmt sich etwas größere Freiheiten bei Vorbildähnlichkeit zugunsten von Lichtstärke und einfachem Einbau

PRO Besteht aus 8-Kanal Steuerung (sofern sinnvoll), Landescheinwerfer(n), eventuell Taxi Scheinwerfer, bis zu zwei Beacons oben/unten (ROT), Positionslichter (ROT+GRÜN+WEISS) und soweit sinnvoll mehrere ACL (WEISS)



ENTRY Consists of 2-Channel control, landing light(s) and a strobe light (usually) white

BASIC Consists of 4-Channel control, landing light(s), basic beacon(RED)/strobe (WHITE) and position light(s) (RED+GREEN)

STANDARD Consists of 4-Channel control, landing light(s), beacon (RED), position lights (RED+GREEN) and, where reasonable, ACL (WHITE). Standard equipment for normal power scale lights

CIVIL/SPORT Consists of 4-Channel control, landing light(s), beacon (RED), position lights (RED+GREEN) combined with ACL (WHITE). This configuration prefers high power and easy-to-mount instead of semi-scale lights.

PRO Consists of 8-Channel control (where reasonable), landing light(s), perhaps taxi spotlights, up to 2 RED beacons top and bottom, position lights (RED+GREEN+WHITE) and, where reasonable, different ACLs